

**FORK OIL 5W** 

Page: 1 / 10

Revision nr: 1.0 Issue date: 09/10/2017

Supersedes:

YMD650490124

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

Product form : Mixture : FORK OIL 5W Trade name/designation Product group : Trade product

#### <u>1.2.</u> Relevant identified uses of the substance or mixture and uses advised against

### Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Lubricant

Function or use category : Lubricants and additives

#### 1.2.2. Uses advised against

No data available

## Details of the supplier of the safety data sheet

JX Nippon Oil & Energy Europe Limited 2F Bury House, 31 Bury Street, London, EC3A 5AR, UK T +44 20 7186 0400 info@ixeurope.com

## Emergency telephone number

**Emergency number** : +44 20-7186-400

Only available during office hours.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	+353 1 809 21 66 (public, 8am - 10pm, 7/7) +353 01 809 2566 (Professionals, 24/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, 24/7, healthcare professionals only)

## **SECTION 2: Hazards identification**

#### Classification of the substance or mixture <u>2.1.</u>

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### <u>2.2.</u> Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.

Extra phrases : EUH208 - Contains Alkoxylated long-chain alkyl amine. May produce an allergic

reaction.

Other hazards 2.3.

Other hazards : Results of PBT and vPvB assessment : Not applicable.



Page : 2 / 10

Revision nr : 1.0

Issue date : 09/10/2017 Supersedes :

# **FORK OIL 5W**

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

## 3.2. Mixtures

Comments

: Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Base oil : distillates hydrotreated heavy paraffinic (DMSO% < 3 %)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index) 649-467-00-8 (REACH-no) 01-2119484627-25-XXXX	>= 50	Asp. Tox. 1, H304
Mineral oil	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8 (EC Index) - (REACH-no) 01-2119487078-27-XXXX	1 - 3	Asp. Tox. 1, H304
Methacrylate copolymers	(CAS-No.) - (EC-No.) - (EC Index) -	1 - 3	Eye Irrit. 2, H319
Alkoxylated long-chain alkyl amine	(CAS-No.) - (EC-No.) - (EC Index) -	< 1	Skin Sens. 1, H317

Full text of H-statements: see section 16

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Additional advice : First aider: Pay attention to self-protection. Concerning personal protective

equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show

this safety data sheet to the doctor in attendance.

Inhalation : Remove person to fresh air and keep comfortable for breathing. In case of doubt or

persistent symptoms, consult always a physician.

Skin contact : Take off contaminated clothing. Gently wash with plenty of soap and water. In case

of doubt or persistent symptoms, consult always a physician.

Eyes contact : Rinse immediately carefully and thoroughly with eye-bath or water. In case of doubt

or persistent symptoms, consult always a physician.

Ingestion : Rinse mouth thoroughly with water. Get medical advice/attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Not expected to present a significant inhalation hazard under anticipated conditions

of normal use. Thermal decomposition can lead to the release of irritating gases and vapours. The following symptoms may occur: Irritating to respiratory system, Cough.

Skin contact : May produce an allergic reaction. The following symptoms may occur: May cause

skin irritation, Redness, Dry skin.

Eyes contact : The following symptoms may occur: May cause slight irritation, Redness, Tears.

Ingestion : The following symptoms may occur: May cause gastrointestinal irritation, nausea,

vomiting and diarrhoea.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



Page: 3 / 10

Revision nr : 1.0

Issue date : 09/10/2017

# **FORK OIL 5W**

Supersedes :

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.

Unsuitable extinguishing media : Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards : Not flammable. Heating causes rise in pressure with risk of bursting.

Hazardous decomposition products in : Carbon oxides (CO, CO2). Phosphorus oxides. Nitrogen oxides. Sulphur oxides.

Hydrogen sulfide. Metal oxides.

### 5.3. Advice for firefighters

case of fire

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain the

extinguishing fluids by bunding. Prevent fire fighting water from entering the

environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus.

Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of

waste in accordance with environmental legislation.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Wear

recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Spilled material may

present a slipping hazard. Avoid contact with skin, eyes and clothing.

#### 6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in

place. Concerning personal protective equipment to use, see section 8.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dam up the liquid spill.

Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and

shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be

disposed of in a safe way, and as per local legislation.

## 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling

: Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment.



Page: 4 / 10
Revision nr: 1.0

Issue date : 09/10/2017

Supersedes :

# **FORK OIL 5W**

Hygiene measures

: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.

Incompatible substances or mixtures

: Strong oxidizing agents. Acids.

Maximum storage duration Storage temperature

: 5 year : <= 40 °C

Heat and ignition sources
Packaging materials

: Keep away from open flames, hot surfaces and sources of ignition.

: Keep only in the original container.

## 7.3. Specific end use(s)

No data available.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Mineral oil (8042-47-5)				
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	5 mg/m³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-respirable fraction)		
Latvia	OEL TWA (mg/m³)	5 mg/m³		
Switzerland	MAK (mg/m³)	5 mg/m³ (inhalable dust)		

Additional information

: Personal air monitoring :. Room air monitoring. Recommended monitoring

procedures

### 8.2. Exposure controls

Engineering measure(s)

: Provide adequate ventilation. Organisational measures to prevent /limit releases,

dispersion and exposure. Safe handling: see section 7.

Personal protective equipment

: The type of protective equipment must be selected according to the concentration

and amount of the dangerous substance at the specific workplace.

Hand protection

: Wear chemically resistant gloves (tested to EN374). Suitable material: PVC (Polyvinyl chloride), Nitrile rubber, Neoprene. Gloves must be replaced after each use and whenever signs of wear or perforation appear. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working

place concentration and quantity of hazardous substances.

Eye protection

: Use suitable eye protection. (EN166): Use splash goggles when eye contact due to splashing is possible

Body protection

: Wear suitable protective clothing.

Respiratory protection

: Not required for normal conditions of use. In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (EN 140). Full face mask (EN 136). Filter type: AP. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must

be used. (EN 137)

Thermal hazard protection

: Not required for normal conditions of use. Use dedicated equipment.

Environmental exposure controls

: Avoid release to the environment. Comply with applicable Community environmental

protection legislation.



Page : 5 / 10

Revision nr : 1.0

Issue date : 09/10/2017
Supersedes :

# **FORK OIL 5W**

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Oily. liquid.
Colour : No data available
Odour : Characteristic.
Odour threshold : No data available
pH : No data available

Relative evaporation rate (butylacetate=1) : < 0,1
Melting / freezing point : -39 °C

Freezing point : No data available

 $\begin{tabular}{ll} Initial boiling point and boiling range & : > 280 °C \\ Flash point & : 185 °C \\ Auto-ignition temperature & : > 240 °C \\ \end{tabular}$ 

Decomposition temperature : No data available
Flammability (solid, gas) : Not applicable,liquid
Vapour pressure : < 0,1 hPa (20°C)
Vapour density : > 1 (20°C) (air=1)
Relative density : No data available
Density : 0,86 - 0,87 kg/l
Solubility : Water: Insoluble

Partition coefficient n-octanol/water : > 3

Kinematic viscosity : 25 - 50 cSt

Dynamic viscosity : No data available

Explosive properties : Not applicable. The study does not need to be conducted because there are no

chemical groups associated with explosive properties present in the molecule.

Oxidising properties : Not applicable. The classification procedure needs not to be applied because there

are no chemical groups present in the molecule which are associated with oxidising

properties.

Explosive limits : 0,6 - 7 vol %

9.2. Other information

VOC content : 0 %

Other properties : Gas/vapour heavier than air at 20°C.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions. Reference to other sections: 10.4 & 10.5.

#### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

## 10.4. Conditions to avoid

Moisture. Overheating. Safe handling: see section 7.

## 10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Safe handling: see section 7.



Page: 6 / 10

Revision nr: 1.0 Issue date: 09/10/2017

Supersedes:

# **FORK OIL 5W**

## **Hazardous decomposition products**

Reference to other sections: 5.2.

## **SECTION 11: Toxicological information**

## Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met.)

, 100.10 107.10119	
Base oil : distillates hydrotreated	heavy paraffinic (DMSO% < 3 %) (64742-54-7)
LD50/oral/rat	> 2000 mg/kg
LD50/dermal/rabbit	> 5000 mg/kg
Mineral oil (8042-47-5)	
LD50/oral/rat	> 5000 mg/kg (OECD 401)
LD50/dermal/rabbit	> 2000 (OECD 402)
LC50/inhalation/4h/rat	> 5000 mg/m³ (aerosol)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met.)
	pH: No data available
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met.)
	pH: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met.)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met.)
Carcinogenicity - Description	: Not classified (Based on available data, the classification criteria are not met.)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met.)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met.)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met.)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met.)
FORK OIL 5W	
Kinematic viscosity	25 - 50 mm²/s
Other information	: Symptoms related to the physical, chemical and toxicological characteristics. For

further information see section 4.

## **SECTION 12: Ecological information**

## **Toxicity**

: According to the criteria of the European classification and labelling system, the Environmental properties substance/the product has not to be labelled as "dangerous for the environment".

Base oil : distillates hydrotreated heavy paraffinic (DMSO% < 3 %) (64742-54-7)			
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)		
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
Mineral oil (8042-47-5)			
LC50 fish 1	(96h) > 10000 mg/l Lepomis macrochirus (Bluegill)		
LL0, fish, acute	100 - 10000 mg/l (96 hours, Information given is based on data obtained from similar substances.)		
EL0, daphnia, acute, Daphnia magna (Big water flea)	100 mg/l (48 hours, Information given is based on data obtained from similar substances.)		
EL0, algae, acute, Pseudokirchneriella subcapitata	100 mg/l (72 hours, Information given is based on data obtained from similar substances.)		
NOELR, algae, Chronic, Pseudokirchneriella subcapitata	100 mg/l (72 hours, Information given is based on data obtained from similar substances.)		
NOELR, daphnia, Chronic, Daphnia magna (Big water flea)	10 - 1000 mg/l (21 days, Information given is based on data obtained from similar substances.)		



Page: 7 / 10
Revision nr: 1.0

Issue date : 09/10/2017

Supersedes:

# **FORK OIL 5W**

### 12.2. Persistence and degradability

FORK OIL 5W		
Persistence and degradability	Not readily biodegradable.	

### 12.3. Bioaccumulative potential

FORK OIL 5W			
Partition coefficient n-octanol/water	> 3		
Bioaccumulative potential	Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.		
Mineral oil (8042-47-5)			
Partition coefficient n-octanol/water > 6			

## 12.4. Mobility in soil

FORK OIL 5W	
Mobility in soil	No data available
Ecology - soil	If product enters soil, it will be mobile and may contaminate groundwater. Floats on water.

### 12.5. Results of PBT and vPvB assessment

FORK OIL 5W	
Results of PBT assessment	No data available

#### 12.6. Other adverse effects

Other adverse effects : No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Avoid release to the environment. Dispose of empty containers and wastes safely. Safe handling: see section 7. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations.

European waste catalogue (2001/573/EC,

75/442/EEC, 91/689/EEC)

This material and its container must be disposed of as hazardous waste

Waste codes should be assigned by the user, preferably in discussion with the waste

disposal authorities.

The following Waste Codes are only suggestions: 130205 - mineral-based non-chlorinated engine, gear and lubricating oils

## **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID		
14.1. UN number	14.1. UN number					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.2. UN proper ship	ping name	•				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.3. Transport haza	rd class(es)	I				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.4. Packing group						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		



Page: 8 / 10

Supersedes:

Revision nr: 1.0

Issue date: 09/10/2017

# **FORK OIL 5W**

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

#### 14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Code: IBC : No data available.

# **SECTION 15: Regulatory information**

## Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Base oil : distillates hydrotreated heavy paraffinic (DMSO% < 3 %) - Mineral oil - Alkoxylated long-chain alkyl amine - Methacrylate copolymers
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Base oil : distillates hydrotreated heavy paraffinic (DMSO% < 3 %) - Mineral oil - Alkoxylated long-chain alkyl amine - Methacrylate copolymers

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0%

### 15.1.2. National regulations

France

Installations classées:

Not applicable.

Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to

VwVwS, Annex 4)

Immission Control Act - 12.BlmSchV

12th Ordinance Implementing the Federal : Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)



Page: 9 / 10 Revision nr: 1.0

Issue date: 09/10/2017

Supersedes:

# **FORK OIL 5W**

#### Netherlands

SZW-lijst van kankerverwekkende stoffen : Mineral oil is listed SZW-lijst van mutagene stoffen : Mineral oil is listed

NIET-limitatieve lijst van voor de

voortplanting giftige stoffen - Borstvoeding

NIET-limitatieve lijst van voor de

voortplanting giftige stoffen -

: None of the components are listed

: None of the components are listed

Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting giftige stoffen - Ontwikkeling : None of the components are listed

#### 15.2. **Chemical safety assessment**

A chemical safety assessment has been carried out for the substance or the mixture by the supplier

For the following substances of this mixture a chemical safety assessment has been carried out

Base oil: distillates hydrotreated heavy paraffinic (DMSO% < 3 %)

Mineral oil

## **SECTION 16: Other information**

Abbreviations and acronyms:

ABM = Algemene beoordelingsmethodiek
ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Code LEL = Lower Explosive Limit/Lower Explosion Limit UEL = Upper Explosion Limit/Upper Explosive Limit REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
BTT = Breakthrough time (maximum wearing time)
DMEL = Derived Minimal Effect level
DNEL = Derived No Effect Level
EC50 = Median Effective Concentration
EL50 = Median effective level
ErC50 = EC50 in terms of reduction of growth rate
ErL50 = EL50 in terms of reduction of growth rate
EWC = European waste catalogue
LC50 = Median lethal concentration
LD50 = Median lethal dose
LL50 = Median lethal level
NA = Not applicable
NOEC = No observed effect concentration
NOEL: no-observed-effect level
NOELR = No observed effect loading rate
NOAEC = No observed adverse effect concentration
NOAEL = No observed adverse effect level
N.O.S. = Not Otherwise Specified
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
 PNEC = Predicted No Effect Concentration
Quantitative structure-activity relationship (QSAR)
STOT = Specific Target Organ Toxicity
 TWA = time weighted average
 VOC = Volatile organic compounds



Page: 10 / 10 Revision nr: 1.0

Issue date: 09/10/2017

Supersedes:

# **FORK OIL 5W**

WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the

datasheet

: ECHA (European Chemicals Agency). Supplier.

Training advice

: Training staff on good practice.

Other information : Assessment/classification CLP. Article 9. Calculation method.

Full text of H- and FUH-statements:

Full text of H- and EoH-statements:				
Asp. Tox. 1	Aspiration hazard, Category 1			
Eye Irrit. 2	Serious eye damage/eye irritation Category 2			
Skin Sens. 1	Skin sensitisation, hazard category 1			
H304	May be fatal if swallowed and enters airways.			
H317	May cause an allergic skin reaction.			
H319	Causes serious eye irritation.			
EUH208	Contains . May produce an allergic reaction.			

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Classification according to Regulation (EC) No. 1272/2008 [CLP] Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.