



Printing date 24.04.2019 Version number 5 Revision: 29.01.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: prestogum Exhaust Repair Paste
- · Article number: 496138, 60310, 603109, 603147, 50589
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

**MOTIP DUPLI GmbH** 

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49/6266/75-0

msds@de.motipdupli.com

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Precautionary statements

P501 Dispose of contents / container in accordance with regional regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7727-43-7	barium sulphate, natural	12.5-<20%
EINECS: 231-784-4	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119491274-35		

(Contd. on page 2)

Printing date 24.04.2019 Version number 5 Revision: 29.01.2019

Trade name: prestogum Exhaust Repair Paste

CAS: 1332-58-7

Kaolin
substance with a Community workplace exposure limit

(Contd. of page 1)
12.5-<20%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 12

(Contd. on page 3)

Printing date 24.04.2019 Version number 5 Revision: 29.01.2019

Trade name: prestogum Exhaust Repair Paste

(Contd. of page 2)

· 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 7727-43-7 barium sulphate, natural

WEL Long-term value: 10\* 4\*\* mg/m³ \*inhalable dust \*\*respirable dust

#### 1332-58-7 Kaolin

WEL Long-term value: 2 mg/m<sup>3</sup>

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not required.
- · Protection of hands:

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g.

KCL Camatril, article no. 898 or similar products

Solvent resistant gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye protection: Goggles recommended during refilling

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Pasty

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

• pH-value at 20 °C (68 °F): 9.8

(Contd. on page 4)

Printing date 24.04.2019 Version number 5 Revision: 29.01.2019

Trade name: prestogum Exhaust Repair Paste

	(Contd. of page		
· Change in condition			
Melting point/freezing point:	Undetermined.		
Initial boiling point and boiling range:	· Undetermined.		
· Flash point:	Not applicable.		
Flammability (solid, gas):	Not applicable.		
Decomposition temperature:	Not determined.		
• Explosive properties: Product does not present an explosion hazard.			
Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
Vapour pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)		
Density at 20 °C (68 °F):	1.68 g/cm³ (14.02 lbs/gal)		
Relative density	Not determined.		
Vapour density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
water:	Not miscible or difficult to mix.		
Partition coefficient: n-octanol/water:	Not determined.		
Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Solvent content:			
Water:	25.8 %		
VOC (EC)	%		
	$0.0~\mathrm{g/l}$		
VOC-EU%	0.00 %		
Solids content:	74.2 %		
9.2 Other information	No further relevant information available.		

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 5)

Printing date 24.04.2019 Version number 5 Revision: 29.01.2019

Trade name: prestogum Exhaust Repair Paste

(Contd. of page 4)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- · European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Safety data sheet available for professional user on request.

SECTION	14: Tran	sport inf	ormati	ion

· ADR, ADN, IMDG, IATA not regulated

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA not regulated

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class not regulated

· 14.4 Packing group

· ADR, IMDG, IATA not regulated

· 14.5 Environmental hazards: Not applicable.

(Contd. on page 6)

Printing date 24.04.2019 Version number 5 Revision: 29.01.2019

Trade name: prestogum Exhaust Repair Paste

(Contd. of page 5)

• 14.6 Special precautions for user Not applicable.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· UN ''Model Regulation'': not regulated

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

\* Data compared to the previous version altered.

GB